

Light efficiency:

94 Lumen/Watt


Light quality:

CRI: 96,8

Color temperature:

3066 K

Output: 378 Lumen



Product name:

PLANK PLUS SPOTLIGHT-3000K-20

Date and time:

18/04/2024 10:34:09


Power consumption:

Power	Power factor
4,0 W	1,0
Voltage (Vcc)	Current
24,0 V	0,168 A


TM-30 details

Rf 95,4
Fidelity index Rf


Rg 102,2
Gamut index Rg



Spectral distribution




CRI R values



White color point

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3066 K	96,8	93,9	95,4	102,2	96,3	0,430	0,397	0,249	0,345	-0,0017

Beam details



Beam angles

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%
20,5°	41°	55,7°

Beam intensities

Peak intensity	Int. ratio in 120° cone	Int. ratio in 90° cone
2139 cd	98,7%	96,5%

Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft
2131lx	533lx	237lx	133lx	85lx	59lx	43lx	33lx	26lx	21lx	18lx	15lx	13lx	11lx	9lx	8lx	7lx	7lx	6lx	5lx
198fcd	49,5fcd	22fcd	12,4fcd	7,9fcd	5,5fcd	4fcd	3,1fcd	2,4fcd	2fcd	1,6fcd	1,4fcd	1,2fcd	1fcd	0,9fcd	0,8fcd	0,7fcd	0,6fcd	0,5fcd	0,5fcd