

# LLS • 30, 60

**182 LED/m • 55 LED/ft**

9,5 W/m • 2,9 W/ft

**182 LED/m • 55 LED/ft**


15,7 W/m • 4,8 W/ft

**182 LED/m • 55 LED/ft**

19,6 W/m • 6,0 W/ft

**30** → Medium 30°

**60** → Wide 60°



**12,8 × 13,4 mm**  
**0,50 × 0,53 "**












# LLS • 30, 60


Prod. name Nome prod.	Product Prodotto	Size Dimensioni (mm • in) (Scale/Scala 1:1)	Light Luce Light distributions/ Distribuzioni della luce	W/m • W/ft
LLS • Medium 30°				9,5 W/m • 2,9 W/ft 15,7 W/m • 4,8 W/ft 19,6 W/m • 6,0 W/ft
LLS • Wide 60°				9,5 W/m • 2,9 W/ft 15,7 W/m • 4,8 W/ft 19,6 W/m • 6,0 W/ft

# LLS • 30, 60




<b>Body</b> Corpo	
<b>Symmetrical linear profile</b> Profilo lineare simmetrico	
<b>Fastening</b> Fissaggio	Caps + Magnets Caps + Steel clips Caps + Adjustable brackets Tappi + Magneti Tappi + Clip in acciaio Tappi + Staffe orientabili
<b>Screen</b> Schermo	Medium 30° Wide 60°
<b>Wiring set</b> Cavo alimentazione	2000 mm • 78,74 "
<b>Ordering length</b> Lunghezza ordinabile	Up to 3000 mm • 118,10 " Fino a 3000 mm
<b>Finishing</b> Finitura	● Grey anodized (Standard) → On request other finishes ● Anodica grigia (Standard) → Su richiesta altre finiture
<b>Listings and marks</b> Certificazioni e marchi	     
<b>Where we produce</b> Dove produciamo	Made in Italy
<b>LED (See page 20)</b> LED (Vedi pagina 20)	  

## Light Luce



<b>Medium 30°</b> 	<b>Light source</b> Sorgente luminosa	182 LED/m • 55 LED/ft	182 LED/m • 55 LED/ft	182 LED/m • 55 LED/ft
	<b>Power consumption</b> Consumo energia	9,5 W/m • 2,9 W/ft	15,7 W/m • 4,8 W/ft	19,6 W/m • 6,0 W/ft
	<b>CCT K</b>	● 1800 ● 2500 ● 3500 ● 2000 ● 2700 ● 4000 ● 2200 ● 3000 ● 5000	● 1800 ● 2500 ● 3500 ● 2000 ● 2700 ● 4000 ● 2200 ● 3000 ● 5000	● 1800 ● 2500 ● 3500 ● 2000 ● 2700 ● 4000 ● 2200 ● 3000 ● 5000
	<b>CRI</b> <b>R9</b> <b>Rf @ 3000 K</b> <b>Rg @ 3000 K</b> <b>MacAdam ellipse</b>	Min 90 Min 50 92 100 3	Min 90 Min 50 92 100 3	Min 90 Min 50 92 100 3
	<b>Delivered lumen output</b> Flusso luminoso emesso ● 3000 K	↓ <b>Medium 30°</b> – 163 lm/W 1544 lm/m • 471 lm/ft	↓ <b>Medium 30°</b> – 160 lm/W 2517 lm/m • 767 lm/ft	↓ <b>Medium 30°</b> – 152 lm/W 2976 lm/m • 907 lm/ft
	<b>Input voltage</b> Tensione di ingresso	24 V DC	24 V DC	24 V DC

# LLS • 30, 60



## Light Luce

<div>Wide 60°</div> <div></div>	<b>Light source</b> Sorgente luminosa	182 LED/m • 55 LED/ft			182 LED/m • 55 LED/ft			182 LED/m • 55 LED/ft		
	<b>Power consumption</b> Consumo energia	9,5 W/m • 2,9 W/ft			15,7 W/m • 4,8 W/ft			19,6 W/m • 6,0 W/ft		
	<b>CCT K</b>	<div><div>● 1800</div><div>● 2000</div><div>● 2200</div></div> <div><div>● 2500</div><div>● 2700</div><div>● 3000</div></div> <div><div>● 3500</div><div>● 4000</div><div>● 5000</div></div>			<div><div>● 1800</div><div>● 2000</div><div>● 2200</div></div> <div><div>● 2500</div><div>● 2700</div><div>● 3000</div></div> <div><div>● 3500</div><div>● 4000</div><div>● 5000</div></div>			<div><div>● 1800</div><div>● 2000</div><div>● 2200</div></div> <div><div>● 2500</div><div>● 2700</div><div>● 3000</div></div> <div><div>● 3500</div><div>● 4000</div><div>● 5000</div></div>		
	<b>CRI</b>	Min 90			Min 90			Min 90		
	<b>R9</b>	Min 50			Min 50			Min 50		
	<b>Rf @ 3000 K</b> <b>Rg @ 3000 K</b> <b>MacAdam ellipse</b>	92 100 3			92 100 3			92 100 3		
	<b>Delivered lumen output</b> Flusso luminoso emesso ● 3000 K	↓ <b>Wide 60°</b> – 165 lm/W 1572 lm/m • 479 lm/ft			↓ <b>Wide 60°</b> – 163 lm/W 2563 lm/m • 781 lm/ft			↓ <b>Wide 60°</b> – 155 lm/W 3030 lm/m • 924 lm/ft		
	<b>Input voltage</b> Tensione di ingresso	24 V DC			24 V DC			24 V DC		



**TAM** Caps + Magnets  
Tappi + Magneti



**TAC** Caps + Steel clips  
Tappi + Clip in acciaio



**TCA** Caps + Adjustable brackets  
Tappi + Staffe orientabili




# LLS • 30, 60


Louvers Louvers

Scale/Scala 1:1


↓ Curved Louvers




15,7 mm  
0,62"



↓ Straight Louvers






15,7 mm  
0,62"



# LLS • 30, 60




Wall cover Copertura murale

Scale/Scala 1:1



# LLS • 30, 60


## Fastening options Opzioni di fissaggio



Order code Codice ordine	
Basic code Codice baset	LLS LLS (Lens Light System)
Light source Sorgente luminosa	1829 182 LED/m • 55 LED/ft 9,5 W/m • 2,9 W/ft 18215 182 LED/m • 55 LED/ft 15,7 W/m • 4,8 W/ft 18220 182 LED/m • 55 LED/ft 19,6 W/m • 6,0 W/ft
CCT K CCT K	18 1800 K 20 2000 K 22 2200 K 25 2500 K 27 2700 K 30 3000 K 35 3500 K 40 4000 K 50 5000 K
Fastening options Opzioni di fissaggio	TAM Caps + Magnets Tappi + Magneti TAC Caps + Steel clips Tappi + Clip in acciaio TCA Caps + Adjustable brackets Tappi + Staffe orientabili
Screen Schermo	M Medium 30° L Wide 60°
Finishing Finitura	01 Grey anodized Anodica grigia
Accessories Accessori	L Louvers/Louvers • Pending W Wall cover/Copertura murale
Order example Esempio ordine	LLS 142 1829 18 TAM M 01 L LLS, 142,0 mm • 5,60 ", 182 LED/m • 55 LED/ft, 9,5 W/m • 2,9 W/ft, Warm White 1800, Caps + Magnets, Medium 30°, Grey anodized, Louvers  LLS, 142,0 mm, 182 LED/m, 9,5 W/m, Warm White 1800, Tappi + Magneti, Medium 30°, Anodica grigia, Louvers



# CRI Typical\* CRI Tipici\*




R9050 – H6 • 3SDCM

High Efficacy

● 3000 K

\* Values taken from sample measurements  
\* Valori presi da misurazioni a campione



CRI Values Valori CRI

CCTK: ● 3000 K

CRI	R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
94,4	99	99	99	99	99	94	93	88	74	99	96	84	99	98	96

## Color Parameters Parametri del colore

Color Temperature	Color Render Index	Red Component	Color Fidelity	Color Gamut	Color Quality Scale	Color Coord. CIE 1931	Color Coord. CIE 1931	Color Coordinate	Color Coordinate	Color Diviation from Black Body
CCT K	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	X	Y	U	V	ΔUV
3042 K	96,2	74,4	92,2	100,5	92,9	0,441	0,399	0,255	0,347	-0,0009




FULL SPECTRUM • 3SDCM

OPTISOLIS™

● 3000 K

\* Values taken from sample measurements  
\* Valori presi da misurazioni a campione



CRI Values Valori CRI


CCTK: ● 3000 K

CRI	R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
97,6	99	98	97	96	99	97	97	97	92	97	94	89	99	98	98

## Color Parameters Parametri del colore

Color Temperature	Color Render Index	Red Component	Color Fidelity	Color Gamut	Color Quality Scale	Color Coord. CIE 1931	Color Coord. CIE 1931	Color Coordinate	Color Coordinate	Color Diviation from Black Body
CCT K	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	X	Y	U	V	ΔUV
3491 K	97,6	92,2	95,2	102,7	96,5	0,404	0,386	0,237	0,339	-0,0019

# Cable outlet Uscita cavi



## Warnings Avvertenze

The installation of the product, must be done as illustrated in the catalogue or inside the technical data-sheet that can be asked to the manufacturer. An installation performed differently from the one indicated may compromise the durability and characteristics of the product itself.

An installation performed differently from the one indicated may compromise the durability and characteristics of the product.

Unsuitable cross-section / length of the cable can negatively affect the lighting power of the product. If Power supplies, even those with a plastic case, are located in spaces that are too small for their dimensions; they will be subjected to dissipation problems that will compromise their functionality. Silicones or resins subjected to temperature changes and used near the product, if not in accordance with the specifications issued by the manufacturer, they can seriously damage the LED component. The products can not be modified without any authorization by the manufacturer.

L'installazione del prodotto, dovrà eseguirsi come illustrato nel catalogo o nella documentazione tecnica richiedibile al produttore. Un'installazione eseguita diversamente da quella indicata, può compromettere la durata e le caratteristiche del prodotto.

Prima dell'installazione verificare la corretta sezione del cavo collegato tra LED e alimentatore.

Sezione / lunghezza del cavo non congrui, possono alterare in negativo la luminosità del prodotto. Gli alimentatori, anche quelli con contenitore plastico, inseriti in spazi troppo piccoli, saranno soggetti a problemi di dissipazione che comprometteranno la loro funzionalità. Siliconi o resine soggetti a sbalzi di temperature e utilizzati in prossimità del prodotto, se non conformi alle specifiche rilasciate dal produttore possono danneggiare gravemente il componente LED. I prodotti non possono essere modificati senza autorizzazione da parte del produttore.