

LLS • Oval

182 LED/m • 55 LED/ft

9,5 W/m • 2,9 W/ft


182 LED/m • 55 LED/ft

15,7 W/m • 4,8 W/ft


182 LED/m • 55 LED/ft

19,6 W/m • 6,0 W/ft

OVAL → (70° × 25°)



12,8 × 16,0 mm
0,50 × 0,63 "



LLS • Oval



Body Corpo

Symmetrical linear profile

Profilo lineare simmetrico

Fastening Fissaggio	Caps + Magnets Caps + Steel clips Caps + Adjustable brackets Tappi + Magneti Tappi + Clip in acciaio Tappi + Staffe orientabili
-------------------------------	--

Screen Schermo	OVAL (70° × 25°)
--------------------------	------------------

Wiring set Cavo alimentazione	2000 mm • 78,74 "
---	-------------------

Ordering length Lunghezza ordinabile	Up to 3000 mm • 118,10 " Fino a 3000 mm
--	--

Finishing Finitura	● Grey anodized (Standard) → On request other finishes ● Anodica grigia (Standard) → Su richiesta altre finiture
------------------------------	---

Listings and marks

Certificazioni e marchi



Where we produce

Dove produciamo

Made in Italy

LED (See page 20)

LED (Vedi pagina 20)



Light Luce



OVAL (70° × 25°)





OVAL (70° × 25°)

Light source Sorgente luminosa	182 LED/m • 55 LED/ft	182 LED/m • 55 LED/ft	182 LED/m • 55 LED/ft
Power consumption Consumo energia	9,5 W/m • 2,9 W/ft	15,7 W/m • 4,8 W/ft	19,6 W/m • 6,0 W/ft
CCT K	● 1800 ● 2500 ● 3500 ● 2000 ● 2700 ● 4000 ● 2200 ● 3000 ● 5000	● 1800 ● 2500 ● 3500 ● 2000 ● 2700 ● 4000 ● 2200 ● 3000 ● 5000	● 1800 ● 2500 ● 3500 ● 2000 ● 2700 ● 4000 ● 2200 ● 3000 ● 5000
CRI R9 Rf @ 3000 K Rg @ 3000 K MacAdam ellipse	Min 90 Min 50 92 100 3	Min 90 Min 50 92 100 3	Min 90 Min 50 92 100 3
Delivered lumen output Flusso luminoso emesso ● 3000 K	↓ Oval (70° × 25°) – 153 lm/W 1454 lm/m • 443 lm/ft	↓ Oval (70° × 25°) – 150 lm/W 2355 lm/m • 718 lm/ft	↓ Oval (70° × 25°) – 149 lm/W 2915 lm/m • 889 lm/ft
Input voltage Tensione di ingresso	24 V DC	24 V DC	24 V DC



TAM Caps + Magnets
Tappi + Magneti






TAC Caps + Steel clips
Tappi + Clip in acciaio





TCA Caps + Adjustable brackets
Tappi + Staffe orientabili



↓ Curved Louvers






↓ Straight Louvers



LLS • Oval

Wall cover Copertura murale

Scale/Scala 1:1




LLS • Oval

Fastening options Opzioni di fissaggio


TAM

Caps + Magnets
Tappi + Magneti




TAC

Caps + Steel clips
Tappi + Clip in acciaio



TCA

Caps + Adjustable brackets
Tappi + Staffe orientabili



Order code Codice ordine

Basic code

Codice base

Light source

Sorgente luminosa

CCT K

CCT K

Fastening options

Opzioni di fissaggio

Screen

Schermo

Finishing

Finitura

Accessories

Accessori

• **LLS** LLS (Lens Light System)

• **1829** 182 LED/m • 55 LED/ft
9,5 W/m • 2,9 W/ft

• **18215** 182 LED/m • 55 LED/ft
15,7 W/m • 4,8 W/ft

• **18220** 182 LED/m • 55 LED/ft
19,6 W/m • 6,0 W/ft

• **18** 1800 K

• **20** 2000 K

• **22** 2200 K

• **25** 2500 K

• **27** 2700 K

• **30** 3000 K

• **35** 3500 K

• **40** 4000 K

• **50** 5000 K

• **TAM** Caps + Magnets
Tappi + Magneti

• **TAC** Caps + Steel clips
Tappi + Clip in acciaio

• **TCA** Caps + Adjustable brackets
Tappi + Staffe orientabili

• **7025** OVAL (70°×25°)

• **01** Grey anodized

• Anodica grigia

• **L** Louvers/Louvers
W Wall cover/Copertura murale

Order example


Esempio ordine

• **LLS 142 1829 18 TAM 7025 01 L**

LLS, 142,0 mm • 5,60",
182 LED/m • 55 LED/ft,
9,5 W/m • 2,9 W/ft, Warm White 1800,
Caps + Magnets, OVAL (70°×25°),
Grey anodized, Louvers

LLS, 142,0 mm, 182 LED/m, 9,5 W/m,
Warm White 1800, Tappi + Magneti,
OVAL (70°×25°), Anodica grigia, Louvers

CRI Typical* CRI Tipici*




R9050 – H6 • 3SDCM

High Efficacy

● 3000 K

* Values taken from sample measurements
* Valori presi da misurazioni a campione



CRI Values Valori CRI

CCTK: ● 3000 K

CRI	R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
94,4	99	99	99	99	99	94	93	88	74	99	96	84	99	98	96

Color Parameters Parametri del colore

Color Temperature	Color Render Index	Red Component	Color Fidelity	Color Gamut	Color Quality Scale	Color Coord. CIE 1931	Color Coord. CIE 1931	Color Coordinate	Color Coordinate	Color Deviation from Black Body
CCT K	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	X	Y	U	V	ΔUV
3042 K	96,2	74,4	92,2	100,5	92,9	0,441	0,399	0,255	0,347	-0,0009




FULL SPECTRUM • 3SDCM

OPTISOLIS™

● 3000 K

* Values taken from sample measurements
* Valori presi da misurazioni a campione



CRI Values Valori CRI

CCTK: ● 3000 K



CRI	R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
97,6	99	98	97	96	99	97	97	97	92	97	94	89	99	98	98

Color Parameters Parametri del colore

Color Temperature	Color Render Index	Red Component	Color Fidelity	Color Gamut	Color Quality Scale	Color Coord. CIE 1931	Color Coord. CIE 1931	Color Coordinate	Color Coordinate	Color Deviation from Black Body
CCT K	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	X	Y	U	V	ΔUV
3491 K	97,6	92,2	95,2	102,7	96,5	0,404	0,386	0,237	0,339	-0,0019

LLS • Oval

Cable outlet Uscita cavi



Scale/Scala 1:1

Warnings Avvertenze

The installation of the product, must be done as illustrated in the catalogue or inside the technical data-sheet that can be asked to the manufacturer. An installation performed differently from the one indicated may compromise the durability and characteristics of the product itself.

An installation performed differently from the one indicated may compromise the durability and characteristics of the product. Unsuitable cross-section / length of the cable can negatively affect the lighting power of the product. If Power supplies, even those with a plastic case, are located in spaces that are too small for their dimensions; they will be subjected to dissipation problems that will compromise their functionality. Silicones or resins subjected to temperature changes and used near the product, if not in accordance with the specifications issued by the manufacturer, they can seriously damage the LED component. The products can not be modified without any authorization by the manufacturer.

L'installazione del prodotto, dovrà eseguirsi come illustrato nel catalogo o nella documentazione tecnica richiedibile al produttore. Un'installazione eseguita diversamente da quella indicata, può compromettere la durata e le caratteristiche del prodotto.

Prima dell'installazione verificare la corretta sezione del cavo collegato tra LED e alimentatore. Sezione / lunghezza del cavo non congrui, possono alterare in negativo la luminosità del prodotto. Gli alimentatori, anche quelli con contenitore plastico, inseriti in spazi troppo piccoli, saranno soggetti a problemi di dissipazione che comprometteranno la loro funzionalità. Siliconi o resine soggetti a sbalzi di temperature e utilizzati in prossimità del prodotto, se non conformi alle specifiche rilasciate dal produttore possono danneggiare gravemente il componente LED. I prodotti non possono essere modificati senza autorizzazione da parte del produttore.